

Low pressure guns

ST-860 low pressure



Spray gun with PEEK seat. Resistant to chemicals.
Max. 210 bar / 30 l/min / 80 °C

R+M Nr.		
200 860 500	1/4" F	1/4" F

ST-810 low pressure



Spray gun with POM seat. Resistant to chemicals.
Max. 140 bar / 30 l/min / 80 °C

R+M Nr.		
200 810 520	1/4" F	3/8" F

Shower head



Chrome-plated brass. Housing plastic.
Hose tail 19 mm (3/4"). Max. 8 bar / 20 °C

R+M Nr.	
500 100	19 mm (3/4")

ST-1200 spray guns



Spray gun with adjustable spray angle. Trigger guard. Max. 24 bar / 100 l/min / 50 °C

R+M Nr.			
201 200 535	brass	1/2" F	



Spray gun with adjustable spray angle. Trigger guard. Max. 24 bar / 100 l/min / 95 °C

R+M Nr.			
201 200 550	stainless steel	1/2" F	

Guns with steplessly variable jet adjustment



Plug 16 mm (universal). Max. 8 bar / 20 °C

R+M Nr.	
726 416	



Spray gun with adjustable spray angle.
Max. 24 bar / 100 l/min / 50 °C

R+M Nr.			
201 200 500	brass	1/2" F	



Spray gun with adjustable spray angle.
Max. 24 bar / 100 l/min / 50 °C

R+M Nr.			
201 200 520	stainless steel	1/2" F	

Guns with eight jet adjustments



Plug 16 mm (universal). Max. 8 bar / 20 °C

R+M Nr.	
726 419	

Repair kits ST-1200



R+M Nr.	
201 200 420	stainless steel



R+M Nr.	
201 200 430	brass

Further models of the spray guns ST-1200
are available on request.

Symbols inlet outlet length material nozzle

ST-500 spray guns for chemicals



Pipe stainless steel. Cone jet nozzle.
Max. 5 bar / 0,38 l/min / 80 °C

R+M Nr.	
200 500 500	RILSAN 8 mm
200 500 520	1/4" F