

Suttner steam guns

The steam guns of the series ST-4000 and ST-860D are the ideal solution for cleaning tasks with steam. Both series are designed for a medium temperature of up to 200 °C and for a working pressure of max. 20 bar. By means of a specifically produced valve housing with 3/4" F made out of aluminium the ST-4000 is suitable for extremely high flow rates. The ST-860D is unbeatable in case of small and medium flow rates.

Apart from being enormously resistant to high temperatures the sealing copolymer is suitable for all liquids based on mineral oil as well as for inorganic acids, alkaline solutions, alcohol and anti-corrosion liquids based on amines and seawater or on their mixtures.

The fact that the hose connection is positioned in the front of the gun positively effects the professional handling with the gun as well as the heat radiation close to hand and body.

ST-4000 steam guns with lance



Professional steam gun ST-4000 with lance 500 mm stainless steel with vented handle ST-9 380 mm and steam low pressure nozzle made out of stainless steel. Max. 20 bar / 200 °C

R+M Nr.	☺	☺
204 000 500	steam low pressure nozzle	3/4" F

ST-860D steam guns



Professional steam gun ST-860D.
Max. 20 bar / 200 °C

R+M Nr.	☺	☺
200 860 550	1/4" F	1/4" F

ST-860D steam guns with lance



Professional steam gun ST-860D with lance 400 mm stainless steel, vented handle ST-9.1 220 mm and nozzle protector ST-12 without nozzle. Max. 20 bar / 200 °C

R+M Nr.	☺	☺
200 860 555	nozzle protector ST-12	1/4" F

Hose reels

Hose reel trolleys

Hose reels for wall mounting

Hose reels for wall mounting

Hose reel trolleys



Powder-coated steel. 2 hose tails 15 mm. Outer diameter = hose length 19 mm = 40 m.
H x D x W = 410 x 480 x 320 mm.
Max. 10 bar

R+M Nr.	☺	☺
762 080 350	3/4" M	3/4" M



Powder-coated steel. 2 hose tails 15 mm. Outer diameter = hose length 19 mm = 40 m.
H x D x W = 730 x 400 x 460 mm.
Max. 10 bar

R+M Nr.	☺	☺
762 080 260	3/4" M	3/4" M



Powder-coated steel. 2 hose tails 15 mm. Outer diameter = hose length 19 mm = 80 m.
H x D x W = 800 x 500 x 460 mm.
Max. 10 bar

R+M Nr.	☺	☺
762 080 130	3/4" M	3/4" M



Plastic. 2 plugs 16 mm (universal). Outer diameter = hose length 18 mm = 50 m.
H x D x W = 750 x 440 x 370 mm.
Max. 6 bar

R+M Nr.		
761 60		

Symbols ☺ inlet ☺ outlet ☺ length ☺ diameter DN nominal diameter ☺ wall thickness