

## Low pressure hoses

### Rubber hoses - per metre



Black surface and interior. Industrial version for water and compressed air. Abrasion- and ozone-resistant. Burst pressure > 60 bar. Max. 20 bar. -10 °C - +60 °C

R+M Nr.	DN	↔	↗
305 10	13 mm (1/2")	100 m	4,0 mm
305 20	19 mm (3/4")	100 m	5,0 mm
305 30	25 mm (1")	100 m	5,0 mm

### Rubber hoses - per metre



Grey NBR surface. White, food safe interior. Suitable for hot and cold liquids. Resistant to animal fats. Burst pressure > 60 bar. Max. 20 bar. -20 °C - +100 °C

R+M Nr.	DN	↔	↗
305 40	13 mm (1/2")	50 m	4,5 mm
305 50	19 mm (3/4")	50 m	4,8 mm

### Plastic hoses - complete units



NTS WHITE PLUS. Yellow surface with blue stripes. White interior. Food safe. PVC water hose with six layers. Abrasion- and UV-resistant. Lead and cadmium free. Burst pressure 30 bar. -20 °C - +65 °C

R+M Nr.	DN	↔	↗
305 112 15	13 mm (1/2")	15 m	2,3 mm
305 112 25	13 mm (1/2")	25 m	2,3 mm
305 112 50	13 mm (1/2")	50 m	2,3 mm
305 134 25	19 mm (3/4")	25 m	2,8 mm
305 134 50	19 mm (3/4")	50 m	2,8 mm

### Reinforced PVC hoses - per metre



Transparent. Max. 60 °C. Other dimensions are available on request

R+M Nr.	DN	↔	↗
306 40	6 mm	100 m	3,0 mm
306 50	8 mm	100 m	3,0 mm
306 55	9 mm	50 m	3,0 mm
306 60	10 mm	50 m	3,0 mm
307 10	12 mm	50 m	3,0 mm
306 70	13 mm	50 m	3,5 mm
306 80	16 mm	50 m	3,0 mm
306 90	19 mm	50 m	3,5 mm

### Spiral line hoses - per metre



Especially for suction. Suitable for vacuum. -10 °C - +50 °C

R+M Nr.	DN	↔	↗
307 519	19 mm (3/4")	25 m	2,6 mm
307 525	25 mm (1")	25 m	2,7 mm
307 532	32 mm (1.1/4")	25 m	2,7 mm
307 538	38 mm (1.1/2")	25 m	2,7 mm
307 550	50 mm (2")	25 m	4,0 mm

### Clear PVC hoses - per metre



Especially for suction of chemicals. Max. 60 °C. Other dimensions are available on request

R+M Nr.	DN	↔	↗
306 10	4 mm	100 m	1,0 mm
306 20	6 mm	100 m	1,5 mm
306 30	8 mm	100 m	2,0 mm

### Reinforced PVC hoses - per metre



Blue. Max. 60 °C. Other dimensions are available on request

R+M Nr.	DN	↔	↗
080 000 310	9 mm	50 m	3,0 mm



Yellow. Max. 60 °C. Other dimensions are available on request

R+M Nr.	DN	↔	↗
080 000 300	6 mm	50 m	3,0 mm
080 000 320	9 mm	50 m	3,0 mm

### Foodjet - food hose



Food hose EN 854. Particularly resistant to animal and poultry fats.

- » Field of application: cleaning hose designed for the food industry.
- » Suitable for: oil, water, water-in-oil emulsions and water mixes with up to 50 % detergent.
- » Surface synthetic rubber. Particularly abrasion-, oil-, ozone-resistant, weatherproof and food safe.
- » Interior synthetic, oil-resistant rubber. Tight textile meshwork.
- » Max. 80 bar. Burst pressure > 240 bar. -40 °C - +150 °C.

R+M Nr.	DN	↔	↗
303 60	12	10 - 95 m	3,5 mm

### blufood® - food hose



Food hose according to 2002/72/EC. Especially designed for industrial foam cleaning applications.

- » Field of application: foam hose and pre-spraying hose in the food industry. Suitable for contact with liquid food products.
- » Suitable for: water and water mixes of usual cleaning detergents.
- » PVC hose with five layers and a flush surface.
- » Reinforcing twofold textile meshwork.
- » Max. 50 bar. Burst pressure > 240 bar. -20 °C - +70 °C.

R+M Nr.	DN	↔	↗
303 70	12	10 - 70 m	5 mm