

Adjustable nozzles



New

Kr

M22 M. Lance with adjustable nozzle. Spray angle 25°. Max. 200 bar / 150 °C

R+M Nr.	D	↔	(M)**	R+M Nr.	D	↔	(M)**
657 340 30	04	430 mm	zinc-plated steel	657 340 309	04	430 mm	stainless steel
657 345 30	045	430 mm	zinc-plated steel	657 345 309	045	430 mm	stainless steel
657 350 30	05	430 mm	zinc-plated steel	657 350 309	05	430 mm	stainless steel
657 355 30	055	430 mm	zinc-plated steel	657 355 309	055	430 mm	stainless steel
657 370 30	07	430 mm	zinc-plated steel	657 370 309	07	430 mm	stainless steel









New

Kr







Plug KW. Lance with adjustable nozzle. Without nozzle. Max. 200 bar / 150 °C

R+M Nr.	↔	(M)**	R+M Nr.	↔	(M)**
657 300 7	600 mm	zinc-plated steel	657 300 79	600 mm	stainless steel

Cleantecs rotating nozzles with carbide insert

HM 500	HM 700	HM 1000
 <p>1/4" F. Spray angle 20°. Max. 500 bar / 100 °C</p>	 <p>1/4" F. Spray angle 20°. Max. 700 bar / 100 °C. Delivery time of approx. 1 week</p>	 <p>1/4" F. Spray angle 20°. Max. 1000 bar / 100 °C. Delivery time of approx. 1 week</p>
<p>Kit HM 500</p> 	<p>Kit HM 700</p> 	<p>Kit HM 1000</p> 

D	R+M Nr.	R+M Nr.	D	R+M Nr.	R+M Nr.	D	R+M Nr.	R+M Nr.
02	655 500 520	655 500 120	02	655 700 520	655 700 120	02	655 100 520	655 100 120
025	655 500 525	655 500 125	025	655 700 525	655 700 125	025	655 100 525	655 100 125
03	655 500 530	655 500 130	03	655 700 530	655 700 130	03	655 100 530	655 100 130
035	655 500 535	655 500 135	035	655 700 535	655 700 135	035	655 100 535	655 100 135
04	655 500 540	655 500 140	04	655 700 540	655 700 140	04	655 100 540	655 100 140
045	655 500 545	655 500 145	045	655 700 545	655 700 145	045	655 100 545	655 100 145
05	655 500 550	655 500 150	05	655 700 550	655 700 150	05	655 100 550	655 100 150
055	655 500 555	655 500 155	055	655 700 555	655 700 155	055	655 100 555	655 100 155
06	655 500 560	655 500 160	06	655 700 560	655 700 160	06	655 100 560	655 100 160
07	655 500 570	655 500 170	07	655 700 570	655 700 170	07	655 100 570	655 100 170

HM 500	HM 500	HM 500
 <p>1/4" F. Spray angle 20°. Max. 500 bar / 100 °C</p>	 <p>M20x1. Spray angle 20°. Max. 500 bar / 100 °C</p>	 <p>M20x1. Spray angle 20°. Max. 500 bar / 100 °C</p>
<p>Kit HM 500</p> 	<p>Kit HM 500</p> 	<p>Kit HM 500</p> 

D	R+M Nr.	R+M Nr.	D	R+M Nr.	R+M Nr.	D	R+M Nr.	R+M Nr.
03	655 500 630	655 500 130	03	655 500 640	655 500 130	05	655 500 650	655 500 150

Symbols **D** nozzle **↔** length **(M)** material