

easyfoam365+ injectors

Metering valves ST-161



Hose tail 9 mm : M14 M. Metering valve ST-161 suitable for being refitted in easyfoam365+ injectors (ST-160, ST-166, ST-167 and ST-168)

R+M Nr.
200 161 500



Hose tail 9 mm : hose tail 9 mm. Panel mount is possible

R+M Nr.
200 161 510

Suction filter ST-31



Filter without check valve. Plastic. Stainless steel weight

R+M Nr.
200 031 615

Suction hose



Per metre. Reinforced PVC hose. Blue. DN 9. 50 m. Max. 60 °C

R+M Nr.
080 000 310

Accessories injectors



Hose tail 9 mm : M14 M. Check valve

R+M Nr.
200 163 350



1/4" M : M14 M. Check valve

R+M Nr.
200 163 355

Injectors ST-160



Coupling ST-45-250 stainless steel : plug ST-45-250 stainless steel. Injector with suction hose 2000 mm and suction filter ST-31. The chemical dosing is adjusted by 8 exchangeable nozzle inserts (0.5 - 2 mm). Max. 250 bar / 90 °C



Coupling ST-45-250 nickel-plated brass : plug ST-45-250 zinc-plated steel. Injector with suction hose 2000 mm and suction filter ST-31. The chemical dosing is adjusted by 8 exchangeable nozzle inserts (0.5 - 2 mm). Max. 250 bar / 90 °C



M22 F : M22 M. Injector with suction hose 2000 mm and suction filter ST-31. The chemical dosing is adjusted by 8 exchangeable nozzle inserts (0.5 - 2 mm). Max. 350 bar / 90 °C

R+M Nr.	D
200 160 815	1,2 mm
200 160 816	1,3 mm
200 160 817	1,4 mm
200 160 818	1,5 mm
200 160 819	1,6 mm
200 160 820	1,7 mm
200 160 821	1,8 mm
200 160 822	1,9 mm
200 160 823	2,0 mm
200 160 824	2,1 mm
200 160 825	2,2 mm
200 160 826	2,3 mm

R+M Nr.	D
200 160 830	1,2 mm
200 160 831	1,3 mm
200 160 832	1,4 mm
200 160 833	1,5 mm
200 160 834	1,6 mm
200 160 835	1,7 mm
200 160 836	1,8 mm
200 160 837	1,9 mm
200 160 838	2,0 mm
200 160 839	2,1 mm
200 160 840	2,2 mm
200 160 841	2,3 mm

R+M Nr.	D
200 160 753	1,2 mm
200 160 754	1,3 mm
200 160 750	1,4 mm
200 160 751	1,5 mm
200 160 752	1,6 mm
200 160 755	1,7 mm
200 160 756	1,8 mm
200 160 757	1,9 mm
200 160 758	2,0 mm
200 160 759	2,1 mm
200 160 760	2,2 mm
200 160 761	2,3 mm

Symbols nozzle